

HZM



HZM 938 FRONT END LOADER



97kW
ENGINE POWER

1.7m³
STND. BUCKET





SPECIFICATIONS

SPECIFICATIONS	Overall weight(kg)	10000
	L×W×H (mm)	7050×2430×3120
	Rated bucket capacity(m ³)	1.7
	Rated load(kg)	3000
	Max. dump height (mm)	3250
	Bucket indicator	Yes
	Max. breakout force(KN)	138
ENGINE	Model	CUMMINS 6BT5.9-C130
	Type	Direct injection, Horizontal, Water-cooled, Six cylinder
	Rated power (kw)	97kW(130hp)
	Rated speed(r/min)	2400
TRANSMISSION	Model of torque converter	BS428 X13
	Type	Single stage,3 elements
	Gearbox type	Axial full power shift transmission
	Gear shift	4 gears ahead,2 gear astern
HYDRAULICS	Distribution of work valve	DF25
	Working pump	CBGj2100,CBGq2100
STEERING	Type	Articulated hydraulic steering
	Max. turning angle	lift and right 36.5±1°
	Min turning radius(mm)	5862
BRAKE SYSTEM	Brake type	Air-break brake
TYRES	Standard tires	17.5-25



KEY FEATURES



CUMMINS ENGINE



HYDR. TORQUE CONVERTER



6-SPEED TRANSMISSION



UPGRADED MAIN VALVE



UPGRADED PUMPS



UPGRADED SOLENOIDS



NEW CABING SUSPENSION



DUAL COOLING SYSTEM



220V WATER PRE-HEATER



CABIN A/C VENTILATION



AIR BRAKE BOOSTERS



VARTA BATTERIES



KEY FEATURES



FRONT WHEEL FENDERS



REAR WHEEL FENDERS



OPERATOR CABIN DOOR



SIDE WINDOWS



UPGRADED CABIN



USB & 12V CHARGER



ITEM & CUP HOLDER



STERIO SYSTEM



FRONT WINDOW DEFROST



ADJUSTABLE SEAT



ADJUSTABLE STEERING



FRONT WORK LIGHTS