

Technical Specifications

Model	ML40
Engine	YANMAR ENGINE
Power	45hp/33.5kw
Fuel	Diesel
Transmission	4WD Hydrostatic
Drive Speed	0-12km/h
Working Hydraulic Flow	33.5L/min x 2
*Max. Lift Height (Extended)	3.207m
*Max. Lift Height (Retracted)	2.509m
Lifting Capacity	1 000kg
Min. Turning Radius	2300mm
Max. Turning Angle	45 degrees
Operating Weight	21 50kg
Fuel Tank Capacity	30L
Battery Capacity	60 Ah
Standard Tires	26x12-12
Overall Dimensions (L*W*H)	2260x1300x2260

Standard Features

- 4WD Direct Drive Hydrostatic Motors
- DBS (Dynamic Block System)
- Self-levelling Telescopic Boom
- Hydraulic Multiconnector/Quick Hitch
- Boom Floating Function
- Multifunctional Hydraulic Joystick
- ROPS-FOPS Closed Cabin
- Removable Steel Canopy
- Adjustable Steering Column
- . Fully Adjustable Seat
- Standard Bucket
- Flexable Articulation

Engine Options



Optional Attachments

There are over 60 attachments to choose from; each with its own unique application.

- *Lifting heights were measured while equipped with standard bucket.
- **Terms and Conditions apply. Under our policy of continuous improvement, MCM reserves the right to change technical data and design without prior notice.