

MCM

RTL30



Technical Specifications

Parameters

Machine	RTL30
Engine	Yunnei YN27
Rated Power / r.p.m	42kW
Rated Torque / r.p.m	202N-m
No. of Cylinders	4
Fuel Tank Capacity	36L
Transmission	Hydraulic Pilot
Load Capacity	3000kg
Load Center	500mm
Wheels (x=driven)	4

Dimensions

Max. Lifting Height (STND.)	3000mm
Free Lift	1125mm
Fork Size	1070x100x45mm
Fork Spread	1100mm
Tilt Angle	8°/10°
Lenght to Fork Face	3900mm
Overall Width	1860mm
Mast Height Fork Lowered	2275mm
Mast Height Fork Raised	5600mm
Overhead Guard Height	2800mm
Operator's Seat Height	1274mm
Min. Turning Radius	4400mm
Load Distance	1130mm
Rear Overhang	1120mm

Other

Under our policy of continuous improvement, we reserve the right to change technical data and design without prior notice.

Performance

Speeds	Max. Travel	22km/h
	Lifting	350mm/sec
	Lowering	400mm/sec
Max. Drawbar Pull	Full Load	20kN
	No Load	16kN
Max. Gradeability	Full Load	18%
	No Load	20%
Operating Weight		4027kg
Tyres Size	Front	20.5/70-16
	Rear	20.5/70-16
Wheelbase		2050mm
Tread	Front	1560mm
	Rear	1560mm
Overhead Guard Clearance		100mm
Counterweight Height		880mm
Underclearance		230mm
Brake		Air Brake
Battery		12/60 V/AH

Diagram

