

MB
THE CRUSHING EVOLUTION

BF120.4 S4 BUCKET CRUSHER

Proudly Distributed by **MCM**



BF120.4 S4

Model Specifications

Proudly Distributed By **MCM**



TECHNICAL SPECIFICATIONS

Recommended excavator	ton	30 - 45
Recommended backhoe loader	ton	-
Weight	ton	4,80
Load capacity	m ³	1,30
Pressure	bar	220 - 280
Back pressure	bar	< 10
Oil flow rate**	l/min	190 - 250
Mouth width	mm	1205
Mouth height	mm	540
Size A	mm	1620
Size B	mm	2185
Size C	mm	1390



PRODUCTIVITY

Crushing output adjustment	m ³ /h
15 mm	15
20 mm	16,4
30 mm	19,2
40 mm	22
50 mm	24,8
60 mm	27,6
70 mm	30,4
80 mm	33
90 mm	36
100 mm	38,8
110 mm	41,6
120 mm	44,4
130 mm	47,2
135 mm	48,6
140 mm	50
145 mm	53

* Installable on the backhoe loader boom only.

** The minimum hydraulic flow rate value must be alongside the required operating pressure.

To obtain the values in ton/h, multiply the data listed in the table by the specific weight of your material. These values are indicative only, estimated with materials of medium load capacity.



WWW.MCMGROUP.CO.ZA

CAPE TOWN

9 Karee Rd, Kraaifontein Industria,
Cape Town, 7570

SALES

(+27) 21 001 8686
ruan@mcmco.co.za

GEORGE

Jura Lands, Beach Road,
Hansmoeskraal, George, 6529

SALES

(+27) 44 878 2917
chris@mcmco.co.za

FREE STATE

Bloem Showgrounds, Curie Avenue,
Generaal De Wet, Bloemfontein, 9301

SALES

(+27) 84 022 7300
clarence@mcmco.co.za

GAUTENG

26 Sterling Rd, Unit 1, Samrand
Business Park, Midrand, 0117

SALES

(+27) 12 030 3451
sales@mcmco.co.za