

MIB[®]

THE CRUSHING EVOLUTION

BF135.8 BUCKET CRUSHER

PROUDLY DISTRIBUTED BY **MCM**





BF135.8

Model Specifications

Proudly Distributed By MCM



TECHNICAL SPECIFICATIONS

Recommended excavator	ton	43 - 80
Recommended backhoe loader	ton	-
Weight	ton	7,50
Load capacity	m ³	1,80
Pressure	bar	230 - 280
Back pressure	bar	< 10
Oil flow rate**	l/min	320 - 380
Mouth width	mm	1300
Mouth height	mm	600
Size A	mm	1880
Size B	mm	3000
Size C	mm	1700



PRODUCTIVITY

Crushing output adjustment	m ³ /h
40 mm	38,7
50 mm	43,2
60 mm	47,6
70 mm	52,2
80 mm	56,6
90 mm	61,1
100 mm	65,6
110 mm	70,1
120 mm	74,5
130 mm	79,1
135 mm	81,3
140 mm	83,5
145 mm	85,7
150 mm	88

* Installable on the backhoe loader boom only.

** The minimum hydraulic flow rate value must be alongside the required operating pressure.

To obtain the values in ton/h, multiply the data listed in the table by the specific weight of your material. These values are indicative only, estimated with materials of medium load capacity.



CAPE TOWN

9 Karee Rd, Kraaifontein Industria, Cape Town, 7570

SALES

(+27) 21 001 8686
ruan@mcmco.co.za

GEORGE

Jura Lands, Beach Road, Hansmoeskraal, George, 6529

SALES

(+27) 44 878 2917
chris@mcmco.co.za

FREE STATE

Bloem Showgrounds, Curie Avenue, Generaal De Wet, Bloemfontein, 9301

SALES

(+27) 84 022 7300
clarence@mcmco.co.za

GAUTENG

26 Sterling Rd, Unit 1, Samrand Business Park, Midrand, 0117

SALES

(+27) 12 030 3451
sales@mcmco.co.za