

MB
THE CRUSHING EVOLUTION

BF150.10 BUCKET CRUSHER

Proudly Distributed by **MCM**



BF150.10

Model Specifications

Proudly Distributed By **MCM**



TECHNICAL SPECIFICATIONS

Recommended excavator	ton	18,5 - 29
Recommended backhoe loader	ton	-
Weight	ton	3,00
Load capacity	m ³	0,70
Pressure	bar	220 - 280
Back pressure	bar	< 10
Oil flow rate**	l/min	150 - 220
Mouth width	mm	1330
Mouth height	mm	830
Size A	mm	1830
Size B	mm	2340
Size C	mm	1655



PRODUCTIVITY

Crushing output adjustment	m ³ /h
15 mm	25
20 mm	29
30 mm	34
40 mm	40
50 mm	47
60 mm	52
70 mm	58
80 mm	64
90 mm	70
100 mm	76
110 mm	83
120 mm	89
130 mm	95
135 mm	100

* Installable on the backhoe loader boom only.

** The minimum hydraulic flow rate value must be alongside the required operating pressure.

To obtain the values in ton/h, multiply the data listed in the table by the specific weight of your material.

These values are indicative only, estimated with materials of medium load capacity.

CAPE TOWN

9 Karee Rd, Kraaifontein Industria,
Cape Town, 7570

SALES

(+27) 21 001 8686
ruan@mcmco.co.za

GEORGE

Jura Lands, Beach Road,
Hansmoeskraal, George, 6529

SALES

(+27) 44 878 2917
chris@mcmco.co.za

FREE STATE

Bloem Showgrounds,
Curie Avenue, Generaal De Wet,
Bloemfontein, 9301

SALES

(+27) 84 022 7300
clarence@mcmco.co.za

GAUTENG

26 Sterling Rd, Unit 1,
Samrand Business Park,
Midrand, 0117

SALES

(+27) 12 030 3451
sales@mcmco.co.za

