

MB[®]
THE CRUSHING EVOLUTION



BF60.1 S4

BUCKET CRUSHER

Proudly Distributed by **MCM**



BF60.1 S4

Model Specifications

Proudly Distributed By MCM



TECHNICAL SPECIFICATIONS

Recommended excavator	ton	10 - 18
Recommended backhoe loader	ton	-
Weight	ton	1,65
Load capacity	m ³	0,55
Pressure	bar	220 - 280
Back pressure	bar	< 10
Oil flow rate**	l/min	120 - 150
Mouth width	mm	610
Mouth height	mm	500
Size A	mm	1000
Size B	mm	1745
Size C	mm	1100



PRODUCTIVITY

Crushing output adjustment	m ³ /h
15 mm	7
20 mm	7,7
30 mm	9
40 mm	10,4
50 mm	11,7
60 mm	13
70 mm	14,4
80 mm	15,8
90 mm	17,1
100 mm	18,5
110 mm	19,8
120 mm	21
130 mm	23

* Installable on the backhoe loader boom only.

** The minimum hydraulic flow rate value must be alongside the required operating pressure.

To obtain the values in ton/h, multiply the data listed in the table by the specific weight of your material.

These values are indicative only, estimated with materials of medium load capacity.

CAPE TOWN

9 Karee Rd, Kraaifontein Industria,
Cape Town, 7570

SALES

(+27) 21 001 8686
ruan@mcmco.co.za

GEORGE

Jura Lands, Beach Road,
Hansmoeskraal, George, 6529

SALES

(+27) 44 878 2917
chris@mcmco.co.za

FREE STATE

Bloem Showgrounds,
Curie Avenue, Generaal De Wet,
Bloemfontein, 9301

SALES

(+27) 84 022 7300
clarence@mcmco.co.za

GAUTENG

26 Sterling Rd, Unit 1,
Samrand Business Park,
Midrand, 0117

SALES

(+27) 12 030 3451
sales@mcmco.co.za