

MB[®]
THE CRUSHING EVOLUTION

BF70.2 S4 BUCKET CRUSHER

Proudly Distributed by **MCM**





BF70.2 S4

Model Specifications

Proudly Distributed By MCM



TECHNICAL SPECIFICATIONS

Recommended excavator	ton	16 - 25
Recommended backhoe loader	ton	-
Weight	ton	2,30
Load capacity	m ³	0,65
Pressure	bar	220 - 280
Back pressure	bar	< 10
Oil flow rate**	l/min	150 - 220
Mouth width	mm	750
Mouth height	mm	510
Size A	mm	1150
Size B	mm	2000
Size C	mm	1200



PRODUCTIVITY

Crushing output adjustment	m ³ /h
15 mm	9
20 mm	10
30 mm	12
40 mm	14
50 mm	16
60 mm	18
70 mm	20
80 mm	22
90 mm	24
100 mm	26
110 mm	28
120 mm	30
130 mm	31

* Installable on the backhoe loader boom only.

** The minimum hydraulic flow rate value must be alongside the required operating pressure.

To obtain the values in ton/h, multiply the data listed in the table by the specific weight of your material.

These values are indicative only, estimated with materials of medium load capacity.



www.MCMGROUP.co.za

CAPE TOWN

9 Karee Rd, Kraaifontein Industria,
Cape Town, 7570

SALES

(+27) 21 001 8686
ruan@mcmco.co.za

GEORGE

Jura Lands, Beach Road,
Hansmoeskraal, George, 6529

SALES

(+27) 44 878 2917
chris@mcmco.co.za

FREE STATE

Bloem Showgrounds, Curie Avenue,
Generaal De Wet, Bloemfontein, 9301

SALES

(+27) 84 022 7300
clarence@mcmco.co.za

GAUTENG

26 Sterling Rd, Unit 1, Samrand
Business Park, Midrand, 0117

SALES

(+27) 12 030 3451
sales@mcmco.co.za