

MTB[®]
THE CRUSHING EVOLUTION

BF80.3 S4 BUCKET CRUSHER

PROUDLY DISTRIBUTED BY **MCM**





BF80.3 S4

Model Specifications

Proudly Distributed By MCM



TECHNICAL SPECIFICATIONS

Recommended excavator	ton	30 - 50
Recommended backhoe loader	ton	-
Weight	ton	6,20
Load capacity	m ³	1,30
Pressure	bar	200 - 250
Back pressure	bar	< 10
Oil flow rate**	l/min	200 - 280
Mouth width	mm	1070
Mouth height	mm	550
Size A	mm	1710
Size B	mm	2900
Size C	mm	1800



PRODUCTIVITY

Crushing output adjustment	m ³ /h
110 mm	37,2
120 mm	39,3
130 mm	44,5
135 mm	47,2
140 mm	49,1
145 mm	51,3
150 mm	53,8
200 mm	65,3

* Installable on the backhoe loader boom only.

** The minimum hydraulic flow rate value must be alongside the required operating pressure.

To obtain the values in ton/h, multiply the data listed in the table by the specific weight of your material.

These values are indicative only, estimated with materials of medium load capacity.

www.MCMGROUP.co.za

CAPE TOWN

9 Karee Rd, Kraaifontein Industria,
Cape Town, 7570

SALES

(+27) 21 001 8686
ruan@mcmco.co.za

GEORGE

Jura Lands, Beach Road,
Hansmoeskraal, George, 6529

SALES

(+27) 44 878 2917
chris@mcmco.co.za

FREE STATE

Bloem Showgrounds,
Curie Avenue, Generaal De Wet,
Bloemfontein, 9301

SALES

(+27) 84 022 7300
clarence@mcmco.co.za

GAUTENG

26 Sterling Rd, Unit 1,
Samrand Business Park,
Midrand, 0117

SALES

(+27) 12 030 3451
sales@mcmco.co.za