

MTC

THE CRUSHING EVOLUTION

BF90.3 S4 BUCKET CRUSHER

PROUDLY DISTRIBUTED BY **MCM**





BF90.3 S4

Model Specifications

Proudly Distributed By MCM



TECHNICAL SPECIFICATIONS

Recommended excavator	ton	21 - 32
Recommended backhoe loader	ton	-
Weight	ton	3,50
Load capacity	m ³	0,90
Pressure	bar	220 - 280
Back pressure	bar	< 10
Oil flow rate**	l/min	180 - 220
Mouth width	mm	910
Mouth height	mm	540
Size A	mm	1340
Size B	mm	2185
Size C	mm	1390



PRODUCTIVITY

Crushing output adjustment	m ³ /h
15 mm	12
20 mm	13,2
30 mm	15,5
40 mm	17,8
50 mm	20
60 mm	22,5
70 mm	24,8
80 mm	27,2
90 mm	29,5
100 mm	31,8
110 mm	34,2
120 mm	36,5
130 mm	38,8
135 mm	41
140 mm	42

* Installable on the backhoe loader boom only.

** The minimum hydraulic flow rate value must be alongside the required operating pressure.

To obtain the values in ton/h, multiply the data listed in the table by the specific weight of your material.

These values are indicative only, estimated with materials of medium load capacity.



www.MCMGROUP.co.za

CAPE TOWN

9 Karee Rd, Kraaifontein Industria,
Cape Town, 7570

SALES

(+27) 21 001 8686
ruan@mcmco.co.za

GEORGE

Jura Lands, Beach Road,
Hansmoeskraal, George, 6529

SALES

(+27) 44 878 2917
chris@mcmco.co.za

FREE STATE

Bloem Showgrounds, Curie Avenue,
Generaal De Wet, Bloemfontein, 9301

SALES

(+27) 84 022 7300
clarence@mcmco.co.za

GAUTENG

26 Sterling Rd, Unit 1, Samrand
Business Park, Midrand, 0117

SALES

(+27) 12 030 3451
sales@mcmco.co.za