

HZM 938

FRONT END LOADER

Proudly Distributed By **MCM**



BUILT TO PERFORM
ENGINEERED TO LAST



POWERFUL. RELIABLE.
PRODUCTIVE.



MAXIMUM EFFICIENCY
LOWER OPERATING COSTS

SCAN FOR MORE INFO



@mcm.company



MCM Group



www.MCMGROUP.co.za

TECHNICAL SPECIFICATIONS

02

PAGE 2

HZM 938 FRONT END LOADER

Proudly Distributed By MCM

1. SPECIFICATIONS

Overall weight(kg)	10000
L×W×H (mm)	7050 × 2430 × 3120
Rated bucket capacity(m³)	1.7
Rated load(kg)	3000
Max. dump height(mm)	3250
Bucket indicator	Yes
Max. breakout force(KN)	138

2. ENGINE

Model	CUMMINS 6BT5.9-C130
Type	Direct injection, Horizontal, Water-cooled, Six cylinder
Rated power (kW)	97kW (130hp)
Rated speed(r/min)	2400

3. TRANSMISSION

Model of torque converter	BS428 X13
Type	Single stage, 3 elements
Gearbox type	Axial full power shift transmission
Gear shift	4 gears ahead, 2 gear astern

4. HYDRAULICS

Distribution of work valve	DF25
Working pump	CBGj2100, CBGq2100

5. STEERING

Type	Articulated hydraulic steering
Max. turning angle	left and right 36.5±1°
Min turning radius(mm)	5862

6. BRAKE SYSTEM

Brake type	Air-break brake
------------	-----------------

7. TYRES

Standard tires	17.5-25
----------------	---------

KEY FEATURES



CUMMINS ENGINE



HYDR. TORQUE CONVERTER



UPGRADED MAIN VALVE



DUAL COOLING SYSTEM



AIR BRAKE BOOSTERS

WWW.MCMGROUP.CO.ZA

CAPE TOWN

9 Karee Rd, Kraaifontein Industria, Cape Town, 7570

SALES (+27) 21 001 8686

ruan@mcmco.co.za

GEORGE

Jura Lands, Beach Road, Hansmoeskraal, George, 6529

SALES (+27) 44 878 2917

chris@mcmco.co.za

FREE STATE

Bloem Showgrounds, Curie Avenue, Generaal De Wet, Bloemfontein, 9301

SALES (+27) 84 022 7300

clarence@mcmco.co.za

GAUTENG

26 Sterling Rd, Unit 1, Samrand Business Park, Midrand, 0117

SALES (+27) 12 030 3451

sales@mcmco.co.za