

MB[®]
THE CRUSHING EVOLUTION

MB-C50 S4 BUCKET CRUSHER

Proudly Distributed by **MCM**



MB-C50 S4

Model Specifications

Proudly Distributed By MCM



TECHNICAL SPECIFICATIONS

Recommended excavator	ton	6,5 - 10
Recommended backhoe loader	ton	8 - 9*
Weight	ton	0,75
Load capacity	m ³	0,15
Pressure	bar	200 - 250
Back pressure	bar	< 10
Oil flow rate**	l/min	90 - 120
Mouth width	mm	590
Mouth height	mm	280
Size A	mm	1000
Size B	mm	1240
Size C	mm	770



PRODUCTIVITY

Crushing output adjustment	m ³ /h
15 mm	4
20 mm	4,8
30 mm	6,3
40 mm	7,8
50 mm	9,3
60 mm	10

* Installable on the backhoe loader boom only.

** The minimum hydraulic flow rate value must be alongside the required operating pressure.

To obtain the values in ton/h, multiply the data listed in the table by the specific weight of your material.

These values are indicative only, estimated with materials of medium load capacity.



www.MCMGROUP.co.za

CAPE TOWN

9 Karee Rd, Kraaifontein Industria,
Cape Town, 7570

SALES

(+27) 21 001 8686
ruan@mcmco.co.za

GEORGE

Jura Lands, Beach Road,
Hansmoeskraal, George, 6529

SALES

(+27) 44 878 2917
chris@mcmco.co.za

FREE STATE

Bloem Showgrounds, Curie Avenue,
Generaal De Wet, Bloemfontein, 9301

SALES

(+27) 84 022 7300
clarence@mcmco.co.za

GAUTENG

26 Sterling Rd, Unit 1,
Samrand Business Park, Midrand, 0117

SALES

(+27) 12 030 3451
sales@mcmco.co.za