

MCM

RTL50



Technical Specifications

Parameters

Machine	RTL50
Model	Yunnei 4102T
Net Peak Power	76kW
No. of Cylinders	4
Fuel Tank Capacity	78L
Rated Torque / r.p.m	364N-m
Wheels (x=driven)	4
Transmission	Hydraulic Pilot

Operation Dimensions

Standard Lifting Height	4500mm
Free lifting Height	1120mm
Standard Fork Size (LxWxT)	1070 x 100 x 45 mm
Fork Spread	1380mm
Tilt Angle	7.5°/8°
Lenght to Fork Face	4380mm
Overall Width	2050mm
Mast Height Fork Lowered	2330mm
Mast Height Fork Raised	5700mm
Overhead Guard Height	2900mm
Load Distance	1250mm
Min. Turning Radius	5520mm
Rear Overhang	1510mm

Performance

Speeds	Max. Travel	28km/h
	Lifting	320mm/sec
	Lowering	420mm/sec
Battery		12/80 V/AH
Max.Drawbar Pull (Full/No Load)		21kN/16.5kN
Max.Gradeability (Full/No Load)		15/20 %
Tire		16/70-20

General

Rated Load Capacity	5000 kg
Operating Weight	6770 kg
Loader Center	500mm
Wheelbase	2335mm
Overhead Guard Clearance	110mm
Underclearance	290mm
Brake	Air Brake

SUPERIOR MATERIAL HANDLING