

DEMOLITION PULVERIZER







SPECIFICATIONS

Δ

| Recommended excavator | ton | 3 - 6,5 |
|-----------------------------------|--------|-----------|
| Recommended backhoe loader | ton | 5 - 7* |
| Recommended skid steer loader** | ton | 3 - 5 |
| Weight | ton | 0,38 |
| Speed/Min. (minimum - maximum) | rpm | 20 - 25 |
| Rotation | Degree | 360° |
| Oil pressure (rotation) | bar | 160 - 200 |
| Oil flow rate (rotation) | l/min | 20 - 25 |
| Oil pressure (opening – closing) | bar | 200 - 300 |
| Oil flow rate (opening – closing) | l/min | 40 - 70 |
| Pick force F1 | ton | 32 |
| Blade force F2 | ton | 87 |
| Ø Maximum Rebar | mm | 25 |
| Size A | mm | 1180 |
| Size B | mm | 330 |
| Size C | mm | 810 |
| Size D | mm | 85 |
| Size E | mm | 500 |
| Size G | mm | 145 |

* Only compatible with the posterior boom of a Backhoe. ** Please verify machine's Rated Operating Capacity.

OPTIONAL ACCESSORIES

Pulverizer Kit

12 V Electrical Kit (for 2 hose functionality)

24 Month Warranty

APPLICATION AREAS



