




DEMOLITION PULVERIZER

MB-PT650



SPECIFICATIONS



Recommended excavator	ton	6,5 - 13
Recommended backhoe loader	ton	6 - 10*
Main frame weight	ton	0.49
Speed/Min. (minimum - maximum)	rpm	20 - 25
Rotation	Degree	360°
Oil pressure (rotation)	bar	160 - 200
Oil flow rate (rotation)	l/min	25 - 35
Oil pressure (opening - closing)	bar	200 - 350
Oil flow rate (opening - closing)	l/min	70 - 100

* Only compatible with the posterior boom of a Backhoe.

JAW KIT



	Crusher Kit	Pulverizer Kit	Shear Kit
Weight	0.18 ton	0.19 ton	0.19 ton
Total weight (with Main frame)	0.68 ton	0.69 ton	0.69 ton
Size A	1045 mm	860 mm	850 mm
Size B	710 mm	710 mm	710 mm
Size C	1425 mm	1465 mm	1440 mm
Size D	220 mm	300 mm	185 mm
Size E	565 mm	550 mm	300 mm
Size H	535 mm	535 mm	420 mm
Pick force F1	35 ton	35 ton	50 ton
Blade force F2	100 ton	100 ton	115 ton
Ø Maximum Rebar	35 mm	35 mm	-

OPTIONAL ACCESSORIES

12 V Electrical Kit (for 2 hose functionality)	24 Month Warranty
--	-------------------

APPLICATION AREAS



Demolitions