

HZM



HZM 25G FRONT END LOADER





SPECIFICATIONS

Specification	Operating Weight(KG)	5840
	Rated Load(KG)	2200-2500
	Rated Bucket Capacity(M³)	1.2
	Max. Working Height(MM)	4600
	Max. Dump Height(MM)	3600
	Min. Dumping Distance(MM)	640
	Max. Dumping Angle	35°
	Max. Tractive Force(kN)	78
	Breakout Force(kN)	75
	Min. Ground Clearance(MM)	320
Engine	Model	Xichai (FAW)
	Rated Power(KW)	80
	Rated Speed(r/min)	N/A
	Type	Water-cooling, Turbo
	Fuel Tank Capacity(L)	70
	No. of Cylinders	4
Transmission System	Type	Hydraulic Pilot
	Gears Forward/Reverse	Forward*4 / Rear*4
	Travel Speed	30 km/h
	Max Torque	384 Nm
	Transfer Case	315 split
	Brake Control	Air Brake
Steering System	Type	Articulated and hydraulic steering
	Max. Turning Angle	35°
	Min. Turning Radius(MM)	3560
	System Pressure	16 Mpa
	Hydraulic Flow Rate	136 L/min
Operation Dimensions	Total Travel Length	6700 mm
	Total Travel Height	3030 mm
	Total Travel Width	2010 mm
	Wheel Track	1710 mm
	Bucket Width	2200 mm
	Rear Trail Width	1800 mm

